




ERBA ISOLANTI srl


Via Liguria n. 34/31 - 20068 Peschiera Borromeo (MI)
 telef. 02/5530.3089 - fax 02/5530.3127

DATE: 15.03.2001	COTTON TAPES WEAVED BORDERED TAPES : LINEN AND TWILL	Code	NRR xx NRV xx NRRSxx
Adj. 25.05.2003		Tech.data sheet	40 1 0 GB
Page: 1 / 1		Group	M

Linen weave



Twill weave



Type REF.	NRR xx 100% cotton	NRV xx 100% mako cotton	NRRSxx 100% cotton
Nominal Thickness:	mm 0,20	mm 0,14	mm 0,30

TYPICAL APPLICATIONS	Oil filled transformers Cables Motor heads To tie coils Other industrial applications Temporary holding device	Oil filled transformers Small dry type transformers	Oil filled transformers Temporary binding of flat copper

TECHNICAL DATA

Breaking strain:	Kg./cm -Width.	11	11	14
Breaking elongation	%	7	7	7
Threads used	Warp /cm	20-22 (Tit 30/2)	38-40 (Tit 80/2)	29-31 (Tit 30/2)
	Weft /cm	8 + 8 (Tit 3/1)	12 + 12 (Tit 50/4)	10 + 10 (Tit 30/1)
Weight/m	g/cm	1,2-1,3	1,1-1,2	1,6-1,7
Texture		Linen	Linen	Twill
Class Temp.		"B" - 130°C if impregnated with B - F varnish or resin.		
Working Temp		105°C	105°C	105°C

PACKING AND BOXES

Inside. Diam.: 40 mm Rolls Length: Mt. 50

Width mm:	10	15	20	25	30	40
Meters per box	500	500	500	500	500	500

NOTES: For higher thermal class please consider polyester or glass yarn tapes.