

# ERBA ISOLANTI srl

Via Liguria n. 34/31 - 20068 Peschiera Borromeo (MI) telef. 02/5530.3089 - fax 02/5530.3127

Pag: 1/1

META ARAMID FIBER FLOC

Scheda 04 7 1 tecnica

Gruppo B

## **DESCRIPTION**

Meta-aramid, (poly meta-phenylenediamineisophtalamide) is a long polyamide chain in whickh most of amide linkages are attached directly to two aromatic rings. The meta oriented phenylene forms bends in a polymer chain, reducing chain rigidity

This flexible polymer chain gives more textile-like qualities while retaining high temeperature properties.



#### **USE**

FNXMA22 fiber is mostly used for filtration systems of high temerature air.

In electromechanical constructions to fill cavities, an make custom made insulation pieces with epoxy or polyester resin.

Good varnish and resin impregnation also because of its particular "dog bone" fiber cross section

## TECHNICAL SPECIFICATIONS

Properties	Unit	Nominal Value	Tolerance
Fiber length	mm	50	± 5
Fineness	dtex	2,2	± 0,20
Tenacity	cN/tex	54	± 4
Elongation at break	%	35	± 10
		self-extinguish fiber	
Extinguishability		and	
		combustion retarding	
Shrinkage at 300°C for 15 minutes	%	6	
Working temp.	°C	220	
Decomposition temp.	°C	> 370	
Breaking temp. of fibers	°C	400 430	
		doesn't melt.	
		carbonizes	

### **AVAILABILITY**

Unit are Kilograms.

Poly bag of kg 30 of Meta aramid fiber Floc, in cartoon

This information is intended only for general guidance in the application of our products. It has been obtained by careful investigation and reprensents the present state of our knowledge and experience. Because of the large number of possible methods of applications and processing we are not able to assume responsability in any one particular case for either the technical results or the patent rights situation applicable to the country under consideration.