

ERBA ISOLANTI srl

Via Liguria n. 34/31 - 20068 Peschiera Borromeo (MI) telef. 02/5530.3089 - fax 02/5530.3127

DATE:	Feb 2, '04	B R F	Codice	BGBRF10
Pag:	1/1	HERRINGBONE GLASS YARN PATTERN TAPE	Scheda tecnica	40 5 3 BRF GB
		UNIDIRECTIONAL ROVING CORDS	Gruppo	Ι

DESCRIPTION

Unidirectional glass yarn roving cords, herringbone yarn pattern wowen with a glass yarn.


APPLICATIONS

Stuffing, blocking coils of flat copper in generators construction of composites, thanks, etc.

PROPERTIES

BRF tape is high conformable, easy to bend in small radius, high absorbtion properties of epoxy and polyester resin. After impregnation and curing it shows very high tensile strenght.





TECHNICAL DATA

TECH (TCHE DITT)				
Reference	U.M.	BGBFR		
Width	mm	10		
Weight	g/m	12		
Thickness	mm	$0.95 \div 1.15$		
Breaking resistance	da N	420		
Elongation	%	2		

AVAILABILITY

On plastic bobbins.with flanges of 500 m. Height 210 mm. Inside diameter 25 mm / Outside diameter 200 mm.

This information is intended only for general guidance in the application of our products. It has been obtained by careful investigation and represents the present state of our knowledge and experience. Because of the large number of possible methods of applications and processing we are not able to assume responsability in any one particular case for either the technical results or the patent rights situation applicable to the country under consideration.