

ERBA ISOLANTI srl

Via Liguria n. 34/31 - 20068 Peschiera Borromeo (MI) telef. 02/5530.3089 - fax 02/5530.3127

DATA: 17.Giu.94

Pag:

41_2_1GB

1

E-BAND TRAFO

REINFORCED KRAFT PAPER

Codice	S68
~	41 2 1GB
tecnica	
Gruppo	N





DESCRIPTION

Two layers of pure kraft paper, laminated with glass threads.

APPLICATION

Winding of coils of oil cooled transformers.

USF

E-BAND TRAFO is winded by hands and glued at end.

TECHNICAL DATA

	Unit	S6820	S6825	S6830
Width	mm	20	25	30
Thickness	mm	0,17	0,17	0,17
Tensile strenght	da N	75	95	115
- paper Elongation	%	2	2	2
- fibers	%	3	3	3
Dielectric strenght dry	KV/mm	8	8	8
Conductivity of acqueous extract	m S/cm	40	40	40
Colour		brown	brown	brown
Insulating class		A	A	A

ORDERING GUIDE

Inside diameter mm 47 - Outside diameter mm 175 - Lenght of rolls m 150					
Width	20	25	30		
Weight of 1 roll (gr)	300	400	500		
Rolls per cartoon	40	32	28		
Meters per cartoon	6.000	4.800	4.200		
Size of packing	mm 390 x 390 x 220				

The statements in this publication are based on our present knowledge and experience. Due to the number of possible influences in the processing and application of our products, these statements do not exempt ther user from making his own tests and experiments. They cannot be taken as legally binding assurance regarding certain properties or suitability for a particular application. Any possible patent rights as well as existing laws and provisions must be observed at the responsability of the user.