



ERBA ISOLANTI srl

Via Liguria n. 34/31 - 20068 Peschiera Borromeo (MI)
 telef. 02/5530.3089 - fax 02/5530.3127

DATA: 06.Lug.93	E-KRAFT-BAND RT Band	Codice SRT
Pag: 1 / 1		Scheda 41.3GB tecnica
		Gruppo N

DESCRIPTION

Structured tape of high strength rayon yarns. The yarns are bound together with a synthetic resin glue that according to our present state of knowledge has no negative influence on impregnating resins or varnish. The RT tape is strongly hygroscopic and can be impregnated very intensively with varnishes or resins. It is suitable for use from thermal class B (+130 °C); in combination with the appropriate impregnation's it is also optimally suitable for use in higher classes.



APPLICATION

For the binding and bandaging of armature and bindings of coils in the manufacturing of electric motors and transformers.

THERMAL CLASS

B (F) For class F motors if impregnated with class F resins or varnish.

TECHNICAL SPECIFICATION

CODE	UM	SRT 4	SRT 6	SRT 8	SRT 11	SRT 14	SRT 16	SRT 18	SRT 22
Width approx.	mm	1,8	2,6	3,5	4,8	6,1	6,9	7,8	9,5
Thickness approx.	mm	0,30	0,30	0,30	0,30	0,30	0,30	0,30	0,30
Tensile Strength	DaN (kp)	20	30	40	55	70	80	90	110
Elongation	%	9	9	9	9	9	9	9	9
Peak temperature	°C	205	205	205	205	205	205	205	205

Ordering guide, packing and boxes

CODICE	UM	SRT 4	SRT 6	SRT 8	SRT 11	SRT 14	SRT 16	SRT 18	SRT 22	
Standard colour		Beige								
Meters per spool	m	1.800	1.000	800	500	400	350	300	250	
Inside Diam.	mm	25								
Outside Diam.	mm	115								
Spool width	mm	140								
Weight Approx.	kg	1,00	0,90	0,90	0,90	0,90	0,80	0,80	0,90	
Packing & Size	n.	12 spools per cartoon				size: 350 x 275 x 225 mm				
Meters per Cartoon	mt	21.600	12.000	9.600	6.000	4.800	4.200	3.600	3.000	

Le notizie contenute nel presente bollettino sono frutto di accurate ricerche e di numerosi esperimenti nel ns laboratorio. Data però la molteplicità delle applicazioni pratiche, esse hanno valore unicamente indicativo, senza alcuna nostra responsabilità.